

Sealed Maintenance Free Lead-Acid Batteries

Supercharge Batteries Pty. Ltd.

Chemwatch Hazard Alert Code: 4

Chemwatch: 4854-29

Version No: 3.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 26/08/2014

Print Date: 17/11/2015

Initial Date: Not Available

L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| | |
|-------------------------------|---|
| Product name | Sealed Maintenance Free Lead-Acid Batteries |
| Synonyms | Exide Valve-Regulated Lead-Acid Battery Sealed Maintenance-Free Non Spillable |
| Proper shipping name | BATTERIES, WET, NON-SPILLABLE, electric storage |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|--------------------------|--|
| Relevant identified uses | Battery. NOTE: The chemical hazards relate to the released contents. Undamaged sealed lithium batteries normally present a low hazard, however damaged batteries may release highly corrosive and toxic contents. Disassembly, abuse or destruction of battery cell may cause violent explosion with scattering of contents. Heating above 85 deg C may cause bursting with release of contents. Heating above 85 deg C will melt lithium with severe fire and explosion hazard. |
|--------------------------|--|

Details of the supplier of the safety data sheet

| | |
|-------------------------|---|
| Registered company name | Supercharge Batteries Pty. Ltd. |
| Address | 1B Chicago Avenue, Blacktown 2148 NSW Australia |
| Telephone | 1300 737 244 |
| Fax | Not Available |
| Website | www.supercharge.com.au |
| Email | Not Available |

Emergency telephone number

| | |
|-----------------------------------|-------------------------|
| Association / Organisation | Chemwatch 24hr TollFree |
| Emergency telephone numbers | 1800 039 008 |
| Other emergency telephone numbers | Not Available |

CHEMWATCH EMERGENCY RESPONSE

| Primary Number | Alternative Number 1 | Alternative Number 2 |
|----------------|----------------------|----------------------|
| 1800 039 008 | +612 9186 1132 | Not Available |

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

| | Min | Max |
|--------------|-----|-----|
| Flammability | 0 | |
| Toxicity | 2 | |
| Body Contact | 4 | |
| Reactivity | 0 | |
| Chronic | 3 | |

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

| | |
|------------------------|--|
| Poisons Schedule | Not Applicable |
| GHS Classification [1] | Metal Corrosion Category 1, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Reproductive Toxicity Category 1A, STOT - SE (Resp. Irr.) Category 3, STOT - RE Category 2, Acute Aquatic Hazard Category 1, Chronic Aquatic Hazard Category 1 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI |

Label elements

Continued...

Sealed Maintenance Free Lead-Acid Batteries

| | |
|--------------------|--|
| GHS label elements | |
|--------------------|--|

| | |
|-------------|---------------|
| SIGNAL WORD | DANGER |
|-------------|---------------|

Hazard statement(s)

| | |
|------|---|
| H290 | May be corrosive to metals |
| H302 | Harmful if swallowed |
| H332 | Harmful if inhaled |
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |
| H360 | May damage fertility or the unborn child |
| H335 | May cause respiratory irritation |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |

Precautionary statement(s) Prevention

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P234 | Keep only in original container. |
| P270 | Do not eat, drink or smoke when using this product. |
| P273 | Avoid release to the environment. |

Precautionary statement(s) Response

| | |
|----------------|--|
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P310 | Immediately call a POISON CENTER or doctor/physician. |
| P363 | Wash contaminated clothing before reuse. |
| P390 | Absorb spillage to prevent material damage. |
| P391 | Collect spillage. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P405 | Store locked up. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

| | |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|---------------|-----------|---------------------------------------|
| Not Available | NotSpec. | Sealed container with electrochemical |
| Not Available | NotSpec. | contents typically, |
| 7439-92-1 | 65-75 | <u>lead</u> |
| 7664-93-9 | 20 | <u>sulfuric acid</u> |
| 7440-31-5 | <0.5 | <u>tin</u> |
| 8047-59-4 | <0.1 | <u>calcium</u> |

Sealed Maintenance Free Lead-Acid Batteries

| | | |
|---------------|----------|---|
| Not Available | 5 | fiberglass separator |
| Not Available | NotSpec. | case material as; |
| 9003-56-9 | 5 | styrene/ butadiene/ acrylonitrile copolymer |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

| | |
|---------------------|--|
| Eye Contact | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▶ Quickly remove all contaminated clothing, including footwear. ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. |
| Ingestion | <ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to strong acids:

- ▶ Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- ▶ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- ▶ Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- ▶ Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the desiccating action of the acid on proteins in specific tissues.

INGESTION:

- ▶ Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- ▶ **DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.**
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- ▶ Charcoal has no place in acid management.
- ▶ Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- ▶ Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- ▶ Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- ▶ Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. **DO NOT use neutralising agents or any other additives.** Several litres of saline are required.
- ▶ Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- ▶ Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

- ▶ Gastric acids solubilise lead and its salts and lead absorption occurs in the small bowel.
- ▶ Particles of less than 1 um diameter are substantially absorbed by the alveoli following inhalation.
- ▶ Lead is distributed to the red blood cells and has a half-life of 35 days. It is subsequently redistributed to soft tissue & bone-stores or eliminated. The kidney accounts for 75% of daily lead loss; integumentary and alimentary losses account for the remainder.
- ▶ Neurasthenic symptoms are the most common symptoms of intoxication. Lead toxicity produces a classic motor neuropathy. Acute encephalopathy appears infrequently in adults. Diazepam is the best drug for seizures.
- ▶ Whole-blood lead is the best measure of recent exposure; free erythrocyte protoporphyrin (FEP) provides the best screening for chronic exposure. Obvious clinical symptoms occur in adults when whole-blood lead exceeds 80 ug/dL.
- ▶ British Anti-Lewisite is an effective antidote and enhances faecal and urinary excretion of lead. The onset of action of BAL is about 30 minutes and most of the chelated metal complex is excreted in 4-6 hours, primarily in the bile. Adverse reaction appears in up to 50% of patients given BAL in doses exceeding 5 mg/kg. CaNa2EDTA has also been used alone or in concert with BAL as an antidote. D-penicillamine is the usual oral agent for mobilisation of bone lead; its use in the treatment of lead poisoning remains investigational. 2,3-dimercapto-1-propanesulfonic acid (DMPS) and dimercaptosuccinic acid (DMSA) are water soluble analogues of BAL and their effectiveness is undergoing review. As a rule, stop BAL if lead decreases below 50 ug/dL; stop CaNa2EDTA if blood lead decreases below 40 ug/dL or urinary lead drops below 2 mg/24hrs.

[Ellenhorn & Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

| Determinant | Index | Sampling Time | Comments |
|---------------------------------|---|------------------------|----------|
| 1. Lead in blood | 30 ug/100 ml | Not Critical | |
| 2. Lead in urine | 150 ug/gm creatinine | Not Critical | B |
| 3. Zinc protoporphyrin in blood | 250 ug/100 ml erythrocytes OR 100 ug/100 ml blood | After 1 month exposure | B |

Continued...

B: Background levels occur in specimens collected from subjects **NOT** exposed.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|---|
| Fire Incompatibility | <ul style="list-style-type: none"> ▶ Keep dry ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically. |
|-----------------------------|---|

Advice for firefighters

| | |
|------------------------------|---|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use fire fighting procedures suitable for surrounding area. ▶ Do not approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use. <p>Slight hazard when exposed to heat, flame and oxidisers.</p> |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ May emit corrosive, poisonous fumes. May emit acrid smoke. <p>Decomposition may produce toxic fumes of; sulfur oxides (SOx) metal oxides</p> |

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| | |
|---------------------|---|
| Minor Spills | <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Secure load if safe to do so. ▶ Bundle/collect recoverable product. ▶ Collect remaining material in containers with covers for disposal. |
| Major Spills | <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Wear protective clothing, safety glasses, dust mask, gloves. ▶ Secure load if safe to do so. Bundle/collect recoverable product. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Water may be used to prevent dusting. ▶ Collect remaining material in containers with covers for disposal. ▶ Flush spill area with water. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

| | |
|--------------------------|--|
| Safe handling | <ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ DO NOT allow material to contact humans, exposed food or food utensils. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
| Other information | <ul style="list-style-type: none"> ▶ DO NOT store near acids, or oxidising agents ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. |

Conditions for safe storage, including any incompatibilities

Sealed Maintenance Free Lead-Acid Batteries

| | |
|--------------------------------|--|
| Suitable container | <ul style="list-style-type: none"> ▶ Lined metal can, lined metal pail/ can. ▶ Plastic pail. ▶ Polyliner drum. ▶ Packing as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks. |
| Storage incompatibility | <ul style="list-style-type: none"> ▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. ▶ Keep dry ▶ NOTE: May develop pressure in containers; open carefully. Vent periodically. |

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|---------------|---------------------------------------|------------|---------------|---------------|---------------|
| Australia Exposure Standards | lead | Lead, inorganic dusts & fumes (as Pb) | 0.15 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | lead | Cadmium and compounds (as Cd) | 0.01 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | sulfuric acid | Sulphuric acid | 1 mg/m3 | 3 mg/m3 | Not Available | Not Available |
| Australia Exposure Standards | tin | Tin, metal | 2 mg/m3 | Not Available | Not Available | Not Available |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|---------------|---------------|---------------|---------------|---------------|
| lead | Lead | 0.15 mg/m3 | 120 mg/m3 | 700 mg/m3 |
| sulfuric acid | Sulfuric acid | Not Available | Not Available | Not Available |
| tin | Tin | 6 mg/m3 | 67 mg/m3 | 400 mg/m3 |
| calcium | Calcium | 30 mg/m3 | 330 mg/m3 | 2000 mg/m3 |


| Ingredient | Original IDLH | Revised IDLH |
|---|---|----------------------|
| Sealed container with electrochemical contents typically, | Not Available | Not Available |
| lead | 700 mg/m3 | 100 mg/m3 |
| sulfuric acid | 80 mg/m3 | 15 mg/m3 |
| tin | Unknown mg/m3 / 400 mg/m3 / Unknown ppm | 25 mg/m3 / 100 mg/m3 |
| calcium | Not Available | Not Available |
| fiberglass separator | Not Available | Not Available |
| case material as; | Not Available | Not Available |
| styrene/ butadiene/ acrylonitrile copolymer | Not Available | Not Available |

MATERIAL DATA

None assigned. Refer to individual constituents.

Exposure controls

| Appropriate engineering controls | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection.</p> <p>Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.</p> <p>An approved self contained breathing apparatus (SCBA) may be required in some situations.</p> <p>Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> | | | | | | | | | | | |
|--|--|---|----------------------|------------|--|------------------------------|---|----------------------------|--|----------------------------|--|------------------------------|
| | | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) |
| | Type of Contaminant: | Air Speed: | | | | | | | | | | |
| | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) | | | | | | | | | | |
| | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | | | | | | | | | | |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | | | | | | | | | | | |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.) | | | | | | | | | | | |
| | <p>Within each range the appropriate value depends on:</p> | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

| | | | | | | | | | | | |
|--|---|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
| | <table border="1"> <tr> <td>Lower end of the range</td> <td>Upper end of the range</td> </tr> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
| Lower end of the range | Upper end of the range | | | | | | | | | | |
| 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | | | | | | | | | | |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | | | | | | | | | | |
| 3: Intermittent, low production. | 3: High production, heavy use | | | | | | | | | | |
| 4: Large hood or large air mass in motion | 4: Small hood-local control only | | | | | | | | | | |
| Personal protection |  | | | | | | | | | | |
| Eye and face protection | <p>None under normal operating conditions.</p> <p>OTHERWISE:</p> <ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] | | | | | | | | | | |
| Skin protection | See Hand protection below | | | | | | | | | | |
| Hands/feet protection | <ul style="list-style-type: none"> ▶ Elbow length PVC gloves <p>Wear safety footwear.</p> | | | | | | | | | | |
| Body protection | See Other protection below | | | | | | | | | | |
| Other protection | <p>No special equipment needed when handling small quantities.</p> <p>OTHERWISE:</p> <ul style="list-style-type: none"> ▶ Overalls. ▶ Barrier cream. ▶ Eyewash unit. | | | | | | | | | | |
| Thermal hazards | Not Available | | | | | | | | | | |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Sealed Maintenance Free Lead-Acid Batteries

| Material | CPI |
|------------------|-----|
| NATURAL RUBBER | A |
| NATURAL+NEOPRENE | A |
| NEOPRENE | A |
| NEOPRENE/NATURAL | A |
| NITRILE | A |
| PE | A |
| PVC | A |
| SARANEX-23 | A |

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|-------------------------|
| up to 10 x ES | E-AUS P2 | - | E-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | E-AUS / Class 1 P2 | - |
| up to 100 x ES | - | E-2 P2 | E-PAPR-2 P2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|----------------------------|-------------------------------------|---------------|
| Appearance | Solid; insoluble in water. | | |
| Physical state | Manufactured | Relative density (Water = 1) | Not Available |

Sealed Maintenance Free Lead-Acid Batteries

| | | | |
|---|----------------|--|----------------|
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Applicable |
| pH (as supplied) | Not Applicable | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Applicable | Viscosity (cSt) | Not Applicable |
| Initial boiling point and boiling range (°C) | Not Applicable | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Applicable | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Applicable |
| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
| Solubility in water (g/L) | Immiscible | pH as a solution (1%) | Not Applicable |
| Vapour density (Air = 1) | Not Applicable | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Contact with alkaline material liberates heat Unstable in the presence of incompatible materials |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

| | |
|---------------------|---|
| Inhaled | <p>Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema. Exposure to high concentrations causes bronchitis and is characterised by the onset of haemorrhagic pulmonary oedema. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.</p> |
| Ingestion | <p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Ingestion of acidic corrosives may produce circumoral burns with a distinct discolouration of the mucous membranes of the mouth, throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Oedema of the epiglottis may produce respiratory distress and possibly, asphyxia. Nausea, vomiting, diarrhoea and a pronounced thirst may occur. More severe exposures may produce a vomitus containing fresh or dark blood and large shreds of mucosa. Shock, with marked hypotension, weak and rapid pulse, shallow respiration and clammy skin may be symptomatic of the exposure. Circulatory collapse may, if left untreated, result in renal failure. Severe cases may show gastric and oesophageal perforation with peritonitis, fever and abdominal rigidity. Stricture of the oesophageal, gastric and pyloric sphincter may occur as within several weeks or may be delayed for years. Death may be rapid and often results from asphyxia, circulatory collapse or aspiration of even minute amounts. Delayed deaths may be due to peritonitis, severe nephritis or pneumonia. Coma and convulsions may be terminal.</p> |
| Skin Contact | <p>Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.</p> |
| Eye | <p>When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Direct eye contact with acid corrosives may produce pain, lachrymation, photophobia and burns. Mild burns of the epithelia generally recover rapidly and completely. Severe burns produce long-lasting and possible irreversible damage. The appearance of the burn may not be apparent for several weeks after the initial contact. The cornea may ultimately become deeply vascularised and opaque resulting in blindness.</p> |
| Chronic | <p>Repeated or prolonged exposure to acids may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.</p> <p>The impact of inhaled acidic agents on the respiratory tract depends upon a number of interrelated factors. These include physicochemical characteristics, e.g., gas versus aerosol; particle size (small particles can penetrate deeper into the lung); water solubility (more soluble agents are more likely to be removed in the nose and mouth). Given the general lack of information on the particle size of aerosols involved in occupational exposures to acids, it is difficult to identify their principal deposition site within the respiratory tract. Acid mists containing particles with a diameter of up to a few micrometers will be deposited in both the upper and lower airways. They are irritating to mucous epithelia, they cause dental erosion, and they produce acute effects in the lungs (symptoms and changes in pulmonary function). Asthmatics appear to be at particular risk for pulmonary effects.</p> <p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests. There is sufficient evidence to establish a causal relationship between human exposure to the material and subsequent developmental toxic effects in the</p> |

Sealed Maintenance Free Lead-Acid Batteries

off-spring.

Exposure to the material may cause concerns for human fertility, generally on the basis that results in animal studies provide sufficient evidence to cause a strong suspicion of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects.

Excessive exposure to lead can affect the blood, the nervous system, heart, endocrine organs and the immune system and the digestive system. The synthesis of haemoglobin is inhibited and can result in anaemia. If left untreated, neuromuscular dysfunction, possible paralysis and encephalopathy (brain tissue damage) may result. Other symptoms of overexposure include joint and muscle pain, weakness of the extensor muscles (frequently the hand and wrist), headache, dizziness, abdominal pain, diarrhoea, constipation, nausea, vomiting, blue line on the gums, insomnia and metallic taste. High body levels produce cerebrospinal pressure, brain damage with stupor leading to coma and, in some cases, death. Early symptoms of lead poisoning ("plumbism") include anorexia and loss of weight, constipation, apathy or irritability, occasional vomiting, fatigue, headache, weakness, and a metallic taste in the mouth. Advanced poisonings are characterised by intermittent vomiting, irritability, nervousness, myalgia of the arms and legs (often with wrist and foot drop). Severe poisonings may produce persistent vomiting, ataxia, stupor or lethargy, visual disturbances progressing to optic neuritis and atrophy, hyper-tension, papilloedema, cranial nerve paralysis, delirium, convulsions and coma. Neurological effects include mental retardation, seizures, cerebral palsy and marked muscular contractions that distort the spine, limbs, hips and sometimes the cranial innervated muscles (dystonia musculorum deformans). Industrial exposure has been associated with irreversible kidney damage.

| | | |
|---|---|---------------------------------|
| Sealed Maintenance Free Lead-Acid Batteries | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| lead | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Nil Reported |
| | Inhalation (rat) LC50: >5.05 mg/l4 h ^[1] | |
| sulfuric acid | TOXICITY | IRRITATION |
| | Inhalation (guinea pig) LC50: 0.018 mg/L/8h ^[2] | Eye (rabbit): 1.38 mg SEVERE |
| | Inhalation (mouse) LC50: 0.32 mg/L/2h ^[2] | Eye (rabbit): 5 mg/30sec SEVERE |
| | Inhalation (rat) LC50: 0.51 mg/L/2hE ^[2] | |
| tin | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Not Available |
| calcium | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >2500 mg/kg ^[1] | Not Available |
| styrene/ butadiene/ acrylonitrile copolymer | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 5010 mg/kg ^[2] | Not Available |
| Legend: | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | |

| | | | |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity | ✓ | Carcinogenicity | ⊖ |
| Skin Irritation/Corrosion | ✓ | Reproductivity | ✓ |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✓ |
| Respiratory or Skin sensitisation | ⊖ | STOT - Repeated Exposure | ✓ |
| Mutagenicity | ⊖ | Aspiration Hazard | ⊖ |

Legend: ✗ – Data available but does not fill the criteria for classification
 ✓ – Data required to make classification available
 ⊖ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| Ingredient | Endpoint | Test Duration (hr) | Species | Value | Source |
|------------|----------|--------------------|-------------------------------|-------------|--------|
| lead | LC50 | 96 | Fish | 0.0079mg/L | 2 |
| lead | EC50 | 48 | Crustacea | 0.029mg/L | 2 |
| lead | EC50 | 72 | Algae or other aquatic plants | 0.0205mg/L | 2 |
| lead | BCFD | 8 | Fish | 4.324mg/L | 4 |
| lead | EC50 | 48 | Algae or other aquatic plants | 0.0217mg/L | 2 |
| lead | NOEC | 672 | Fish | 0.00003mg/L | 4 |

Continued...

Sealed Maintenance Free Lead-Acid Batteries

| | | | | | |
|--|------|------|-------------------------------|-------------|---|
| sulfuric acid | LC50 | 96 | Fish | =8mg/L | 1 |
| sulfuric acid | EC50 | 48 | Crustacea | =42.5mg/L | 1 |
| sulfuric acid | EC50 | 72 | Algae or other aquatic plants | >100mg/L | 2 |
| sulfuric acid | EC50 | 240 | Algae or other aquatic plants | 2.5000mg/L | 4 |
| sulfuric acid | NOEC | 1560 | Fish | 0.025mg/L | 2 |
| tin | LC50 | 96 | Fish | >0.0124mg/L | 2 |
| tin | EC50 | 48 | Crustacea | 0.00018mg/L | 5 |
| tin | EC50 | 72 | Algae or other aquatic plants | >0.0192mg/L | 2 |
| tin | EC50 | 72 | Algae or other aquatic plants | >0.0192mg/L | 2 |
| tin | NOEC | 168 | Crustacea | <0.005mg/L | 2 |
| calcium | EC50 | 48 | Crustacea | 49.1mg/L | 2 |
| calcium | EC50 | 24 | Crustacea | 6934mg/L | 5 |
| calcium | NOEC | 336 | Crustacea | 32mg/L | 2 |
| styrene/ butadiene/ acrylonitrile copolymer | LC50 | 96 | Fish | 11.5mg/L | 4 |

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------|---------------------------------------|---------------------------------------|
| | No Data available for all ingredients | No Data available for all ingredients |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------|---------------------------------------|
| | No Data available for all ingredients |

Mobility in soil

| Ingredient | Mobility |
|------------|---------------------------------------|
| | No Data available for all ingredients |



SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

| Product / Packaging disposal | |
|------------------------------|---|
| | <ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product. |

SECTION 14 TRANSPORT INFORMATION

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant |  |
| HAZCHEM | 2R |

Land transport (ADG)

| | | | | | |
|----------------------------|--|-------|---|---------|----------------|
| UN number | 2800 | | | | |
| Packing group | Not Applicable | | | | |
| UN proper shipping name | BATTERIES, WET, NON-SPILLABLE, electric storage | | | | |
| Environmental hazard | No relevant data | | | | |
| Transport hazard class(es) | <table border="0"> <tr> <td>Class</td> <td>8</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table> | Class | 8 | Subrisk | Not Applicable |
| Class | 8 | | | | |
| Subrisk | Not Applicable | | | | |

| | | |
|------------------------------|--------------------|-----|
| Special precautions for user | Special provisions | 238 |
| | Limited quantity | 1 L |

Air transport (ICAO-IATA / DGR)

| | | |
|------------------------------|---|----------------|
| UN number | 2800 | |
| Packing group | Not Applicable | |
| UN proper shipping name | Batteries, wet, non-spillable electric storage † | |
| Environmental hazard | No relevant data | |
| Transport hazard class(es) | ICAO/IATA Class | 8 |
| | ICAO / IATA Subrisk | Not Applicable |
| | ERG Code | 8L |
| Special precautions for user | Special provisions | A48A67A164A183 |
| | Cargo Only Packing Instructions | 872 |
| | Cargo Only Maximum Qty / Pack | No Limit |
| | Passenger and Cargo Packing Instructions | 872 |
| | Passenger and Cargo Maximum Qty / Pack | No Limit |
| | Passenger and Cargo Limited Quantity Packing Instructions | Forbidden |
| | Passenger and Cargo Limited Maximum Qty / Pack | Forbidden |

Sea transport (IMDG-Code / GGVSee)

| | | |
|------------------------------|--|----------------|
| UN number | 2800 | |
| Packing group | Not Applicable | |
| UN proper shipping name | BATTERIES, WET, NON-SPILLABLE electric storage | |
| Environmental hazard | Marine Pollutant | |
| Transport hazard class(es) | IMDG Class | 8 |
| | IMDG Subrisk | Not Applicable |
| Special precautions for user | EMS Number | F-A, S-B |
| | Special provisions | 29 238 |
| | Limited Quantities | 1 L |

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

| Source | Ingredient | Pollution Category |
|---|---------------|--------------------|
| IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk | sulfuric acid | Y |

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture****LEAD(7439-92-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

| | |
|--|---|
| Australia Exposure Standards | Australia Inventory of Chemical Substances (AICS) |
| Australia Hazardous Substances Information System - Consolidated Lists | International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs |

SULFURIC ACID(7664-93-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|---|
| Australia Exposure Standards | International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs |
| Australia Hazardous Substances Information System - Consolidated Lists | International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft |
| Australia Inventory of Chemical Substances (AICS) | |

TIN(7440-31-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|---|
| Australia Exposure Standards | Australia Inventory of Chemical Substances (AICS) |
| Australia Hazardous Substances Information System - Consolidated Lists | |

CALCIUM(8047-59-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|---|
| Australia Hazardous Substances Information System - Consolidated Lists | Australia Inventory of Chemical Substances (AICS) |
|--|---|

STYRENE/ BUTADIENE/ ACRYLONITRILE COPOLYMER(9003-56-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|---|---|
| Australia Inventory of Chemical Substances (AICS) | International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft |
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | |

| | |
|--------------------|--------|
| National Inventory | Status |
|--------------------|--------|

Sealed Maintenance Free Lead-Acid Batteries

| | |
|-------------------------------|---|
| Australia - AICS | Y |
| Canada - DSL | Y |
| Canada - NDSL | N (styrene/ butadiene/ acrylonitrile copolymer; lead; calcium; sulfuric acid; tin) |
| China - IECSC | Y |
| Europe - EINEC / ELINCS / NLP | N (styrene/ butadiene/ acrylonitrile copolymer) |
| Japan - ENCS | N (calcium; tin) |
| Korea - KECI | Y |
| New Zealand - NZIoC | Y |
| Philippines - PICCS | Y |
| USA - TSCA | Y |
| Legend: | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets) |

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

| Name | CAS No |
|---------|----------------------|
| calcium | 7440-70-2, 8047-59-4 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL: No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.